

PRODUCT DATA SHEET

Supermastic-3

ONE COMPONENT DURABLE MASTIC BASED ON POLYBUTENE AND VEGETABLE OILS

DESCRIPTION

Supermastic-3 is a one component durable mastic based on polybutene and vegetable oils. Within 48 hours of application a paintable surface skin will be formed

USES

Supermastic-3 was developed to seal joints that are subject to low movement and no mechanical exposure. Suitable for interior use as a bedding compound for single glazing.

CHARACTERISTICS / ADVANTAGES

Water resistant and weatherproof

PRODUCT INFORMATION

Packaging	600 ml unipac/ 20 pcs per box
Colour	white
Shelf life	12 months when stored as recommended in original unopened packaging.
Storage conditions	Store between +5 °C and +25 °C and in shaded conditions. Shelf life is 12 months when stored as recommended in original unopened packaging.
Density	1,7-1,8
Service Temperature	+5 °C to +40 °C

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

All surfaces must be clean, dry and free of dust, grease and other loose material.

Adhesion tests prior to application are recommended.

CLEANING OF EQUIPMENT

Clean all tools and application equipment immediately after use with Sika® Remover-208. Once cured, hardened material can only be removed mechanically.

For cleaning skin use Sika® Cleaning Wipes-100.

IMPORTANT CONSIDERATIONS

Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates.

Not suitable for continuous water load

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer

to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

PRODUCT DATA SHEET

Supermastic-3

January 2020, Version 01.0

020511080000000001

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Services AG

Tüffenwies 16
8048 Zürich
Tel: +41 58 436 4040
www.sika.com



PRODUCT DATA SHEET

Supermastic-3

January 2020, Version 01.0
020511080000000001