

# SikaBit® PRO E40 -20 Sand IT

## DECLARATION OF PERFORMANCE No. 39341121

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:</b>	39341121
2	<b>INTENDED USE/S</b>	EN 13969:2004/A2:2006 Flexible sheets for waterproofing – Bitumen damp proof sheets including bitumen basement tanking sheets
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 2+ System 3 for reaction to fire
6a	<b>HARMONISED STANDARD:</b>	EN 13969:2004/A2:2006
	Notified body/ies:	1370, 0987

### Declaration of Performance

SikaBit® PRO E40 -20 Sand IT

39341121

2021.01 , ver. 01

1520

---

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	EN 13969:2004/A1:2006
Watertightness	≥ 60 kPa	System 2+	
Tensile properties:			
Maximum tensile force – L/T	700/500N/50mm -20%	System 2+	
Elongation – L/T	40/45 % -15% (v.a.)		
Impact Resistance	≥ 1000 mm	System 2+	
Resistance to tearing	160/200N – 30 %	System 2+	
Joint strength	600/400N/50mm -20% or out	System 2+	
Resistance to static loading	≥ 15 kg	System 2+	
Durability of watertightness:			
Against artificial ageing	NPD	System 2+	
Against chemicals	NPD		
Low temperature flexibility	≤ -20 °C	System 2+	
Dangerous substances	Asbestos and tar free	System 2+	

---

---

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

---

Name : Salvatore Schirinzi  
Function: General Manager  
At Castel d’Azzano on 13 Gennaio 2021

Name : Carlo Biroli  
Function: PE  
At Castel d’Azzano on 13 Gennaio 2021

.....

.....

---

End of information as required by Regulation (EU) No 305/2011

**RELATED DECLARATION OF PERFORMANCE****Declaration of Performance**

SikaBit® PRO E40 -20 Sand IT

39341121

2021.01 , ver. 01

1520

Product Name	Harmonised technical specification	DoP Number
SikaBit® Pro E40 -20 Sand IT	EN 13707:2009+2A:2009	83274715



20

Sika Services AG, Zurich, Switzerland

DoP No. 39341121

EN 13969:2004/A1:2006

Notified Body 1370, 0987

Flexible sheets for waterproofing – Bitumen damp proof sheets including bitumen basement tanking sheets

Reaction to fire	Class E
Watertightness	≥ 60 kPa
Tensile properties:	
Maximum tensile force – L/T	700/500 N/50mm -20%
Elongation – L/T	40/45 % -15% (v.a.)
Resistance to static loading	≥ 15 kg
Impact Resistance	≥ 1000 mm
Resistance to tearing	160/200 N – 30 %
Joint strength	600/400 N/50mm -20% or out
Low temperature flexibility	≤ -20 °C
Dangerous substances	Asbestos and tar free

<http://dop.sika.com>

#### Declaration of Performance

SikaBit® PRO E40 -20 Sand IT

39341121

2021.01 , ver. 01

1520

---

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

---

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

---

### Sika Services AG

Tüffenwies 16-22  
8064 Zürich  
Switzerland  
[www.sika.com](http://www.sika.com)

### Declaration of Performance

SikaBit® PRO E40 -20 Sand IT

39341121

2021.01 , ver. 01

1520