

# SikaBit® PRO T-625

## **DECLARATION OF PERFORMANCE**

No. 19173832

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	19173832		
2	INTENDED USE/S	EN 13707:2004+A2:2009 Flexible sheets for waterproofing - Reinforced bitumen sheets for roof waterproofing		
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich		
4	AUTHORISED REPRESENTATIVE:			
5	SYSTEM/S OF AVCP:	P: System 2+ System 3 for reaction to fire System 4 for external fire performance		
6a	HARMONISED STANDARD:	EN 13707:2004+A2:2009		
	Notified body/ies:	1370, 0987		

SikaBit® PRO T-625 19173832 2021.04, ver. 01 1520

#### 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
External fire performance	Froof	System 4	EN 13707:2004+A 2:2009
Reaction to fire	Class E	System 3	
Watertightness	≥ 60 kPa	System 2+	
Tensile properties: maximum tensile force - L/T elongation - L/T	750/600 N/50mm - 20 % 45 % - 15 % (v.a.)	System 2+	
Root resistance	NPD	System 2+	
Resistance to static loading	≥ 15 kg	System 2+	
Resistance to impact	≥ 500 mm	System 2+	
Tear resistance	215/215N-30%	System 2+	
Joint strength: Peel adhesion of joints - L/T Shear adhesion of joints - L/T	100 N/50 mm ± 20 % 600/500 N/50mm - 20%	System 2+	
Durability: flexibility at low temperature UV artificial ageing	NPD NPD	System 2+	
Pliability	≤ - 20 °C	System 2+	_
Dangerous substances	Asbestos and tars free	System 2+	_

### 8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Tomasz Gutowski Function: Corporate Standardization

and Approvals

At Warsaw on 16 April 2021

Name: Tatiana Ageyeva

Function: Standardization and Approvals

At Warsaw on 16 April 2021

.....

End of information as required by Regulation (EU) No 305/2011





20

Sika Services AG, Zurich, Switzerland

19173832

EN 13707:2004+A2:2009

Notified Body 1370, 0987

Flexible sheets for waterproofing - Reinforced bitumen sheets for roof waterproofing

External fire performance Froof

Reaction to fire Class E

Watertightness  $\geq 60 \text{ kPa}$ 

Tensile properties:

maximum tensile force - L/T 750/600 N/50mm - 20 %

elongation - L/T 45 % - 15 % (v.a.)

Resistance to static loading  $\geq$  15 kg Resistance to impact  $\geq$  500 mm

Tear resistance 215/215 N - 30 %

Joint strength:

Peel adhesion of joints - L/T  $100 \text{ N/50 mm} \pm 20 \%$ Shear adhesion of joints - L/T 600/500 N/50mm - 20%

Pliability ≤ - 20 °C

Dangerous substances Asbestos and tars free

http://dop.sika.com

### **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

**Declaration of Performance** 

SikaBit® PRO T-625 19173832 2021.04, ver. 01 1520



### **LEGAL NOTE**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All or ders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland www.sika.com

Declaration of Performance SikaBit® PRO T-625 19173832 2021.04 , ver. 01 1520

