

## PRODUCT DATA SHEET

# Sikaplan® WT Control Socket 6 PE

### FPO-PE FLANGE FOR CONTROL AND INJECTION

#### DESCRIPTION

Sikaplan® WT Control Socket 6 PE is a flange element with round base plate and hose connection socket on base of FPO-PE.

#### USES

Sikaplan® WT Control Socket 6 PE is used as injection port, heat welded to Sikaplan® WT sheet membranes, connected to an injection hose for the use as leak- and vacuum control as well as injection access to seal leaks in basement and tunnel waterproofing membranes.

#### CHARACTERISTICS / ADVANTAGES

- Solid base plate that does not deform while placing the concrete
- No concrete underflow
- Compatible with Sikaplan® WT (FPO-PE) membranes
- Heat weldable
- Easy and quick installation

#### APPROVALS / CERTIFICATES

Quality management system EN ISO 9001

#### PRODUCT INFORMATION

##### Packaging

40 pcs / cardboard box

##### Appearance / Colour

Yellow, preformed piece with round base plate and hose connection socket, incl. hose connection piece



##### Shelf life

5 years shelf life from date of production if stored properly in undamaged, unopened, original sealed packaging.

##### Storage conditions

Pieces must be stored in their original packaging and in cool and dry condi-

tions. They must be protected from direct sunlight, rain, snow and ice, etc.

**Diameter** 180 mm

**Unit weight** 0.080 kg

## SYSTEMS

### System Structure

Ancillary products:

- Sikaplan W Control Tube PU
- Sikaplan W Injection Piece
- Sikaplan W Connection Piece
- Sikaplan W Lock Cap
- Sikaplan W Lock Connection Cap
- Sika® Injection 306
- Sika® Injection 701

## APPLICATION INFORMATION

**Ambient Air Temperature** + 5 °C min.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

Installed Sikaplan® WT sheet membrane must be dry and clean.

### APPLICATION METHOD / TOOLS

Installation according to valid Method Statement and standard detail drawing for basement and tunnel waterproofing with Sikaplan® WT sheet membranes. Spotwise heat welding of base plate onto single-layer sheet membrane, or all-around welding of base plate onto second layer of double-layer systems including membrane opening below flange. Connection of the injection hose to the flange:



## IMPORTANT CONSIDERATIONS

This product must only be used by Sika® approved contractors. This product is not compatible with Sikaplan® WT 4220, and Sikaplan® WT 5300 sheet mem-

brane series.

## BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w)

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SikaplanWTControlSocket6PE-en-SE-(02-2020)-1-1.pdf

